

The power behind competitiveness

# Delta UPS-Amplon Family

INX Series, Very Long Backup Models, Single Phase  
1/ 2/ 3kVA

## Reliability for the most critical moments

The INX series is an online double-conversion UPS providing consistent sine-wave power to your critical equipment's. The INX series features an input power factor corrector and best-in-class AC-AC efficiency of up to 91% resulting in greater energy savings. The INX series leads the industry in combining compact size, availability, flexibility and low total cost of ownership.

## Availability

- True online double-conversion topology and zero transfer time to battery for high reliability
- High input power factor corrector ( $> 0.99$ ) for controlled sine wave AC output
- Cold-start capability with temporary battery power when the utility power is out
- Automatic bypass to transfer the load on mains in case of overload and internal fault
- Charging current extended up to 16A

## Flexibility

- Programmable outlets available for non-critical loads
- EPO function available with this model
- Excellent local communications through user friendly LCD display
- Intelligent management software connectivity via RS232, mini slot or USB port
- Three multi-functional buttons for the operation and selection of parameters

## Low Total Cost of Ownership

- Long backup time model with super charger inside the UPS
- Protection against over voltage & charger working even when the UPS is in standby mode
- ECO mode to provide energy cost savings
- Wide input voltage range to reduce the chance of using the battery and to extend battery life
- Intelligent battery management sustaining battery life and performance
- Fan speed control by load level and room temperature to optimize performance
- Automatic shutdown when the power consumption is less than 5%



Sever



Network



Security



Home  
Appliances



POS



Banking



# Delta UPS-Amplon Family

INX Series, Very Long Backup Models, Single Phase  
1/ 2/ 3kVA

Model		INX-1K	INX-2K	INX-3K
Power Rating				
Input	Nominal Voltage	230 Vac		
	Voltage range	110 ~ 300 Vac*		
	Frequency	40 ~ 70 Hz		
	Power Factor	> 0.99 @ nominal voltage (input voltage)		
Output	Power Factor	0.9		
	Voltage	200**/ 208**/ 220/ 230/ 240 Vac		
	Voltage Regulation	± 1% (Battery mode)		
	Frequency	47 ~ 53 Hz or 57 ~ 63 Hz (Synchronized Range)		
	Current Harmonic Distortion	≤ 2% (linear load); ≤ 4% (non-linear load)		
	Overload Capability	100% ~ 110%: warning only; 110% ~ 130%: 2 minutes; 130% ~ 140%: 30 seconds; >140%: 1.5 seconds only		
	Crest Factor	3:1		
Receptacle		Indian socket x 3	Indian socket x 3	Indian socket x 4
Efficiency	Online Mode	89%	90%	91%
Battery Voltage		36 Vdc	72 Vdc	72 Vdc
Charge Current		1/ 2/ 4/ 6/ 8/ 10/ 12/ 14/ 16A		
Audible Noise		< 50dBA @ 1 meter		
Display		LCD		
Communication		Mini Slot x 1, RS-232 Port x 1, USB Port x 1, EPO x 1		
Interfaces				
Dimensions (D x W x H)		397 x 145 x 220 mm		421 x 190 x 318 mm
Weight		5.5 kg	6.4 kg	13.1 kg
Environment	Operating Temperature	0 ~ 40°C		
	Relative Humidity	20% ~ 95% (non-condensing)		

\* At 110 ~ 160 Vac, linear de-rating between 60 ~ 100% load is required.

\*\* De-rate capacity to 80% when the output voltage is adjusted to 200 Vac or 208 Vac.

Please refer to the rating label for the safety rating.

All specifications are subject to change without prior notice.



User-friendly LCD Panel



Very Long Backup Models



Rear panel



Facility Monitoring Software -  
InfraSuite Device Master



Delta offers full range UPS solutions  
from 600 VA to 4000 kVA to fulfill your  
power security needs.



2007~2008  
Forbes Asia's  
Fabulous 50



2009  
Frost & Sullivan  
Green Excellence  
Award for corporate  
Leadership



ISO 9001:2015



ISO 14001:2015



OHSAS 18001:2007



ISO 14064-1:2012

RoHS